

## FEATURES

- Heavy-Duty 4-Post Lift with 6.3 t (14,000 lbs) lifting capacity
- Electric-air control operation system
- Mechanical self-lock and air-driven safety release
- Electrical hydraulic power system, cable-driven
- Skid proof diamond platform
- Two adjustable turnable positions to accommodate different wheel base
- Adjustable platform and adjustable safety lock ladders
- Dual safety device: In case the primary safety locks are out of operation, the lift would also be locked automatically by a second safety device



Designed and Engineered  
**IN THE USA**


Model	Lifting Capacity	Lifting Time	A	B	C	D	E	Gross Weight	Motor
			Overall Length (Inc Ramps)	Overall Length (No Ramps)	Overall Width	Width Between Columns	Lifting Height		
R4P-14K	6.5 t (14,000 lbs)	60 Seconds	6541 mm (257 1/2")	5500 mm (216 1/2")	3324mm (130 7/8")	2946mm (116")	1865mm (73 1/2")	1.25 t (2,756 lbs)	4.0 HP
R4P-14KA	6.5 t (14,000 lbs)	60 Seconds	6528 mm (257")	5500 mm (216 1/2")	3324mm (130 7/8")	2946mm (116")	1915 mm (75 3/8")	1.5 t (3,320 lbs)	4.0 HP

## DETAILS



**EXCLUSIVE FEATURE!**  
**Electric Control Device With UP LOCK and DOWN buttons**

With C.E. stop switch at 300 mm from ground and alarm tone when lowering down from 300 mm to ground make the lift more safety.




**Optional**  
Extension platform for model R4P-14K to add the length of platform up to 610mm (24")


Extension kits for model R4P-14K and R4P-14KA



Even though all cylinders are flow restricted inside, we are adding the flow controlled valve to control the lowering speed for the heavy-duty line four post lifts model R4P-14K and R4P-14KA



**Optional**  
Extension platform for model R4P-14KA to add the wheel base for alignment up to 970mm(38")



Oil-water separator and Solenoid Air Valve are installed outside the control box



**Optional Air Line Kits**  
All four post lifts are designed to use the air line kits for rolling jack. kits No: 40102



**Optional**  
Rolling Jack J6A 2.7 t (6000 lbs) or RJ-8A with Air pump and 1.5" 3" extension adapters included Capacity: 8,000 lbs (3.6 t)



**Optional Turnplate**  
Each Alignment lifts need one set (two pcs.) of turnplates kits No. : 40101