

## FEATURES

- Heavy-Duty 4-Post Lift with 4.0 t (9,000 lbs) lifting capacity
- Electric-air control operation system
- Mechanical self-lock and air-driven safety release
- Electrical hydraulic power system, cable-driven
- Non-Skid diamond platform
- Adjustable platform and adjustable safety lock ladders
- Dual safety device: In case the primary safety locks are out of operation, the lift would also be locked automatically by a second safety device
- Optional Jack



Designed and Engineered  
**IN THE USA**

## SPECIFICATION


Model	Lifting Capacity	Lifting Time	A	B	C	D	E	Gross Weight	Motor
			Overall Length (Inc Ramps)	Overall Length (No Ramps)	Overall Width	Width Between Columns	Lifting Height		
R4P-9K	4.0 t (9,000 lbs)	45 Seconds	5512 mm (217)	4600 mm (181 1/8")	3208mm (126- 1/4")	2852mm (112-1/4")	1865mm (73 1/2")	945 Kg (2,083 lbs.)	2.0/3.0 HP
R4P-9KA	4.0 t (9,000 lbs)	45 Seconds	5512 mm (217)	4600 mm (181 1/8")	3208mm (126- 1/4")	2852mm (112-1/4")	1915mm (75 3/8")	1155 Kg (2,546 lbs.)	2.0/3.0 HP

## DETAILS



**EXCLUSIVE FEATURE!**  
Electric Control Device With UP LOCK and DOWN buttons

With C.E. stop switch at 300 mm from ground and alarm tone when lowering down from 300 mm to ground make the lift more safety.




**Optional**  
Extension platform for model R4P-9K to add the length of platform up to 610mm (24")




Even though all cylinders are flow restricted inside, we are adding the flow controlled valve to control the lowering speed for the heavy-duty line four post lifts model R4P-9K and R4P-9KA



**Optional Air Line Kits**  
All four post lifts are designed to use the air line kits for rolling jack. kits No: 40102



Oil-water separator and Solenoid Air Valve are installed outside the control box



**Optional**  
Rolling Jack J6A 2.7 t (6000 lbs) or RJ-8A with Air pump and 1.5" 3" extension adapters included Capacity: 8,000 lbs (3.6 t)